

	DESCRIPTION	UNIT	1.5Tr Class_3 star Series	
	Model Name		Toushi Plus 3200XL	Toushi 3200XL
	Model Number		RAS.E318PCAIBS	RAS.E318PCAIBW
	Tonnage	TR	1.5	1.5
	Star Rating		3	3
	Compressor	Type / Refrigerant	Rotary / R32	Rotary / R32
Performance	Rated Cooling (100 % load)	BTU/Hr (Watts)	17710 (5190)	17710 (5190)
	Maximum Cooling	BTU/Hr (Watts)	18700 (5480)	18700 (5480)
	Rated ISEER		3.92	3.92
	Annual Power Consumption (As per BEE Norms)	(kWh)	1024.34	1024.34
	Fan Speed	No. of steps	5	5
	Air Flow (IDU) (Cooling-Super High)	CFM	530	530
	Sound level *1	dbA	34	34
Electrical	Rated Power Supply	Volts / Hz / Phase	230 / 50 / 1	230 / 50 / 1
	Rated Power Input	Watts	1940	1940
	Rated Current Drawn	Amps	8.88	8.88
Key Features	Ice Clean (Frost wash)			
	Surround Cooling *2 (Long Air throw)			
	Ambience Light			
	Odour free air (Soft Dry)		√	√
	Silent air		√	√
	AQ-tiv Ion (Ionizer)			
	airCloud Home -Wifi Enabled			
	4 Way Air Swing			
Advanced Features	Hexa Sensor			
	My Mode		√	√
	Powerful Mode		√	√
	One Touch Super Silent		√	√
	ECO Mode (Sensorless)		√	√
	Good Sleep / Sleep mode		√	√
	On / Off Timer		√	√
	Real Time Clock/ On/Off timer (24 hours)			
	Tropical Design		√	√
	100% Inner Grooved Copper Tubes		√	√
	Superslit Fins		√	√
	Filter clean indicator		√	√
	Superfine Mesh filter		√	√
	Up/Down Swing		√	√
	Stabilizer Free Operation		√	√
Hydrophilic Fins (Indoor Unit)		√	√	
Backlight Remote controller		√	√	
Assurance	Compressor Warranty	1 + 9 Years	√	√
	Controller (PCB) Warranty	1 + 4 Years	√	√
	Warranty on Entire Machine	1 Year	√	√
	Compressor Warranty	1 + 4 Years		
Dimensions	Dimension (IDU) (WXHxD)	mm	950 X 294 X 230	950 X 294 X 230
	Dimension (ODU) (WXHxD)	mm	750 X 550 X 290	750 X 550 X 290
	Suction Line Diameter	mm (Inches)	12.7(1/2")	12.7(1/2")
	Liquid Line Diameter	mm (Inches)	6.35(1/4")	6.35(1/4")
	Net Weight IDU /ODU	Kg	10/27.4	10/27.4
Notes:				
Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.				
*1 At Super Silent fan speed & at a distance of 1 m.				
*2 Air flow range for surround cooling will vary as per chassis/ tonnage.				
Permissible maximum pipe length limit is up to 25 mtrs				
Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.				
T&C apply. Offer available on select models only and subject to company's discretion.				
Offer can be withdrawn anytime without prior notice.				

	Description	Unit	1.0Tr. Class_3 star Series		
	Model Name		iZen 3400FXL	iKasu 3400FXL	TOUSHI PLUS 3200XL
	Model Number		RAS.G312PCAISF	RAS.G312PCAIBFE	RAS.E312PCAIBS
	Star Rating		3	3	3
	Compressor	Type / Refrigerant	Rotary / R32	Rotary / R32	Rotary / R32
Performance	Rated Cooling (100 % load)	BTU/Hr (Watts)	11800 (3458)	11800 (3458)	11800 (3458)
	Maximum Cooling	BTU/Hr (Watts)	12600 (3692)	12600 (3692)	12600 (3692)
	Rated ISEER		4.00	4.00	4.00
	Annual Power Consumption (As per BEE Norms)	(kWh)	669.16	669.16	669.16
	Fan Speed	No. of steps	5	5	5
	Air Flow (IDU) (Cooling-Super High)	CFM	406	406	406
	Sound level *1	dbA	32	32	32
	Rated Power Supply	Volts / Hz / Phase	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1
	Rated Power Input	Watts	1095	1095	1095
	Rated Current Drawn	Amps	5.00	5.00	5.00
Key Features	Bigger IDU - 1050 mm				
	Dual Louver				
	Ice Clean (FrostWash)		✓	✓	
	AQ-tv Ion (Ionizer)				
	airCloud Home -Wifi Enabled				
	4 Way Swing				
	Xpandable		✓	✓	✓
	Long air throw *2		✓	✓	✓
	Ambience Light		✓	✓	
	Odour-free air (Soft Dry)		✓	✓	✓
Silent air (Wave Blade Design)		✓	✓	✓	
Remote Features	My Mode		✓	✓	✓
	Backlight Remote controller		✓	✓	✓
	Powerful Mode		✓	✓	✓
	One Touch Super Silent		✓	✓	✓
	ECO Mode		✓	✓	✓
	Good Sleep mode		✓	✓	✓
	On / Off Timer		✓	✓	✓
	Real Time Clock/ On/Off timer (24 hours)		✓*	✓*	✓*
	Hexa Sensor		✓	✓	✓**
	Tropical Design up to 52C		✓	✓	✓
Advance Features	100% Inner Grooved Copper Tubes		✓	✓	✓
	SuperSilt Fins		✓	✓	✓
	Filter clean indicator		✓	✓	✓
	SuperFine Mesh filter		✓	✓	✓
	Up/Down Swing		✓	✓	✓
	Stabilizer Free Operation		✓	✓	✓
	Hydrophilic Fins (Indoor Unit)		✓	✓	✓
	Compressor Warranty	1 + 9 Years	✓	✓	✓
	Controller (PCB) Warranty	1 + 4 Years	✓	✓	✓
	Warranty on Entire Machine	1 Year	✓	✓	✓
Dimensions	Dimension (IDU) (W x H x D)	mm	780 x 280 x 227	780 x 280 x 222	780 x 280 x 222
	Dimension (ODU) (W x H x D)	mm	658 x 530 x 274	658 x 530 x 274	658 x 530 x 274
	Suction Line Diameter	mm (Inches)	9.52(3/8")	9.52(3/8")	9.52(3/8")
	Liquid Line Diameter	mm (Inches)	6.35(1/4")	6.35(1/4")	6.35(1/4")
	Net Weight IDU /ODU	Kg	7.8/24.4	7.8/24.4	7.8/24.4

Notes:

Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.

*1 At Super Silent fan speed & at a distance of 1 m.

*2 Air flow range for long air throw will vary as per chassis/ tonnage, 24 mtr. in 1050 mm, 18 mtr. in 950 mm & 12 mtr. in 780 mm in fan mode. Permissible maximum pipe length limit is up to 25 mtrs

Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

#T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

**T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

Description		Unit	1.5Tr Class_3 star Series				
Model Name			iZen 35005WXL	iZen 34005XL	iZen 3400FXL	iKasu 3400FXL	Toushi Plus 3200XL
Model Number			RAS.V318PCBISH	RAS.G318PCBISS	RAS.G318PCBSF	RAS.G318PCBIF	RAS.E318PCBIB
Star Rating			3	3	3	3	3
Compressor		Type / Refrigerant	ROTARY / R32	ROTARY / R32	ROTARY / R32	ROTARY / R32	ROTARY / R32
Rated Cooling (100 % load)		BTU/Hr (Watts)	17060 (5000)	17060 (5000)	17060 (5000)	17060 (5000)	17060 (5000)
Maximum Cooling		BTU/Hr (Watts)	18084 (5300)	18084 (5300)	18084 (5300)	18084 (5300)	18084 (5300)
Rated ISEER			3.82	3.82	3.82	3.82	3.82
Annual Power Consumption (As per BEE Norms)		(kWh)	1012.62	1012.62	1012.62	1012.62	1012.62
Fan Speed		No. of steps	5	5	5	5	5
Air Flow (IDU) (Cooling-Super High)		CFM	530	530	530	530	530
Sound level *1		dbA	34	34	34	34	34
Rated Power Supply		Volts / Hz / Phase	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1
Rated Power Input		Watts	1940	1940	1940	1940	1940
Rated Current Drawn		Amps	8.8	8.8	8.8	8.8	8.8
Bigger IDU - 1050 mm							
Dual Louver							
Ice Clean (Frost wash)			✓	✓	✓	✓	
AQ-tv Ion (Ionizer)							
airCloud Home -WiFi Enabled			✓				
4 Way Swing			✓	✓			
Xpandable+			✓		✓	✓	✓
Long air throw *2			✓	✓	✓	✓	✓
Ambience Light				✓	✓	✓	
Odour free air (Soft Dry)			✓	✓	✓	✓	✓
Silent air (Wave Blade Design)			✓	✓	✓	✓	✓
My Mode			✓	✓	✓	✓	✓
Backlight Remote controller			✓	✓	✓	✓	✓
Powerful Mode			✓	✓	✓	✓	✓
One Touch Super Silent			✓	✓	✓	✓	✓
ECO Mode			✓	✓	✓	✓	✓
Good Sleep mode			✓	✓	✓	✓	✓
On / Off Timer			✓	✓	✓	✓	✓
Real Time Clock/ On/Off timer (24 hours)			✓	✓	✓*	✓*	✓*
Hexa Sensor			✓	✓	✓	✓	✓**
Tropical Design up to 52°C			✓	✓	✓	✓	✓
100% Inner Grooved Copper Tubes			✓	✓	✓	✓	✓
SuperSilt Fins			✓	✓	✓	✓	✓
Filter clean indicator			✓	✓	✓	✓	✓
SuperFine Mesh filter			✓	✓	✓	✓	✓
Up/Down Swing			✓	✓	✓	✓	✓
Stabilizer Free Operation			✓	✓	✓	✓	✓
Hydrophilic Fins (Indoor Unit)			✓	✓	✓	✓	✓
Compressor Warranty			✓	✓	✓	✓	✓
Controller (PCB) Warranty			✓	✓	✓	✓	✓
Warranty on Entire Machine			✓	✓	✓	✓	✓
Dimension (IDU) (W x H x D)		mm	950 x 294 x 235	950 x 294 x 235	950 x 294 x 235	950 x 294 x 230	950 x 294 x 230
Dimension (ODU) (W x H x D)		mm	750 x 550 x 290	750 x 550 x 290	750 x 550 x 290	750 x 550 x 290	750 x 550 x 290
Suction Line Diameter		mm (Inches)	12.7(1/2")	12.7(1/2")	12.7(1/2")	12.7(1/2")	12.7(1/2")
Liquid Line Diameter		mm (Inches)	6.35(1/4")	6.35(1/4")	6.35(1/4")	6.35(1/4")	6.35(1/4")
Net Weight IDU /ODU		Kg	10.0/27.4	10.0/27.4	10.0/27.4	10.0/27.4	10.0/27.4

Notes:

Unit performance conforms to IS1391-2.

Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant.

*1 At Super Silent fan speed & at a distance of 1 m.

*2 Air flow range for long air throw will vary as per chassis/ tonnage, 24 mtr. in 1050 mm, 18 mtr. in 950 mm & 12 mtr. in 780 mm in fan mode.

Permissible maximum pipe length limit is up to 25 mtrs. Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

#T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

*It indicates that unit has 12 hour On/Off timer.

Description		Unit	2.0Tr Class_3 star Series				
Model Name			iZen 3500SWXL	iZen 3400SXL	iZen 3400FXL	iKasu 3400FXL	Toushi Plus 3200XL
Model Number			RAS.V322PCBISH	RAS.G322PCBIS	RAS.G322PCBISF	RAS.G322PCBIBF	RAS.E322PCBIB
Star Rating			3	3	3	3	3
Compressor		Type / Refrigerant	Twin Rotary / R32	Twin Rotary / R32	Twin Rotary / R32	Twin Rotary / R32	Twin Rotary / R32
Rated Cooling (100 % load)		BTU/Hr (Watts)	21500 (6300)	21500 (6300)	21500 (6300)	21500 (6300)	21500 (6300)
Maximum Cooling		BTU/Hr (Watts)	23000 (6740)	23000 (6740)	23000 (6740)	23000 (6740)	23000 (6740)
Rated ISEER			3.82	3.82	3.82	3.82	3.82
Annual Power Consumption (As per BEE Norms)		(kWh)	1277.22	1277.22	1277.22	1277.22	1277.22
Fan Speed		No. of steps	5	5	5	5	5
Air Flow (IDU) (Cooling-Super High)		CFM	530	530	530	530	530
Sound level *1		dbA	37	37	37	37	37
Rated Power Supply		Volts / Hz / Phase	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1
Rated Power Input		Watts	2235	2235	2235	2235	2235
Rated Current Drawn		Amps	10.23	10.23	10.23	10.23	10.23
Bigger IDU - 1050 mm							
Dual Louver							
Ice Clean (FrostWash)			√	√	√	√	
AQ-tv Ion (Ionizer)							
airCloud Home -Wifi Enabled			√				
4 Way Swing			√	√			
Xpandable+			√	√	√	√	√
Long air throw *2			√	√	√	√	√
Ambience Light			√	√	√	√	
Odour-free air (Soft Dry)			√	√	√	√	√
Silent air (Wave Blade Design)			√	√	√	√	√
My Mode			√	√	√	√	√
Backlight Remote controller			√	√	√	√	√
Powerful Mode			√	√	√	√	√
One Touch Super Silent			√	√	√	√	√
ECO Mode			√	√	√	√	√
Good Sleep mode			√	√	√	√	√
On / Off Timer			√	√	√	√	√
Real Time Clock/ On/Off timer (24 hours)			√	√	√*	√*	√*
Hexa Sensor			√	√	√	√	√**
Tropical Design up to 52C			√	√	√	√	√
100% Inner Grooved Copper Tubes			√	√	√	√	√
SuperSilt Fins			√	√	√	√	√
Filter clean indicator			√	√	√	√	√
SuperFine Mesh filter			√	√	√	√	√
Up/Down Swing			√	√	√	√	√
Stabilizer Free Operation			√	√	√	√	√
Hydrophilic Fins (Indoor Unit)			√	√	√	√	√
Compressor Warranty		1 + 9 Years	√	√	√	√	√
Controller (PCB) Warranty		1 + 4 Years	√	√	√	√	√
Warranty on Entire Machine		1 Year	√	√	√	√	√
Dimension (IDU) (W x H x D)		mm	950 x 294 x 235	950 x 294 x 235	950 x 294 x 235	950 x 294 x 230	950 x 294 x 230
Dimension (ODU) (W x H x D)		mm	800 x 640 x 298	800 x 640 x 298	800 x 640 x 298	800 x 640 x 298	800 x 640 x 298
Suction Line Diameter		mm (Inches)	12.7(1/2")	12.7(1/2")	12.7(1/2")	12.7(1/2")	12.7(1/2")
Liquid Line Diameter		mm (Inches)	6.35(1/4")	6.35(1/4")	6.35(1/4")	6.35(1/4")	6.35(1/4")
Net Weight IDU /ODU		Kg	9.6/32.9	9.6/32.9	9.6/32.9	9.6/32.9	9.6/32.9

NOTES:
Unit performance conforms to IS1391-2.
Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant.
*1 At Super Silent fan speed & at a distance of 1 m.
*2 Air flow range for long air throw will vary as per chassis/ tonnage, 24 mtr. in 1050 mm, 18 mtr. in 950 mm & 12 mtr. in 780 mm in fan mode.
Permissible maximum pipe length limit is up to 25 mtrs. Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.
#T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.
*Ht indicates that unit has 12 hour On/Off timer.
**Ht indicates that the model has pentra sensor.