

# ELEGANTE HEAVY DUTY SERIES



**HSU24E-TXS3BE-INV**

## KEY FEATURES



Supersonic Cooling in 10 Sec.

**Triple inverter<sup>+</sup>**

Triple Inverter Plus Technology



99.9% STERILIZATION  
Frost Self Clean Technology



Hyper PCB



Super Anti-Corrosion



60°C  
Cooling at Extreme Temperature



12 years compressor warranty\*



HEAVY DUTY



1.6 Ton - 5 Star



100% GROOVED COPPER

**5 YEARS**

Comprehensive Warranty

**HSU19E-TXW5BE-INV**



## KEY FEATURES



Supersonic Cooling in 10 Sec.

**Triple inverter<sup>+</sup>**

Triple Inverter Plus Technology

**7 IN 1**

Intelli Convertible 7 in 1



Hyper PCB



Super Anti-Corrosion



60°C  
Cooling at Extreme Temperature



12 years compressor warranty\*

SPECIFICATION	DESCRIPTION	UNITS	ELEGANTE HEAVY DUTY				
			Model Name	HSU24E-TXS3BE-INV	HSU19E-TXW5BE-INV HSU19E-TXS5BE-INV HSU19E-TXG5BE-INV	HSU19E-TXG4BE-INV	HSU13E-TXW5BE-INV HSU13E-TXS5BE-INV HSU13E-TXG5BE-INV
Capacity	Max Cooling	Watts	7000	6000	6000	4000	3850
	100% Cooling	Watts	6350	5400	5300	3500	3500
	50% Cooling	Watts	3175	2700	2650	1750	1750
	Min Cooling	-	1500	900	1000	500	1000
	Heating	Watts	NA	NA	NA	NA	NA
Electrical Rating	Power Supply	Volt/Phase/Hz.	230/Single/50	230/Single/50	230/Single/50	230/Single/50	230/Single/50
	Power Input (100% Cooling)	Watts	2095	1455	1445	925	985
	Rated Current (100% Cooling)	A	9.29	6.46	6.41	4.10	4.37
Performance	ISEER	W/W	3.85	5.05	4.45	5.05	4.45
	Energy Star	-	3	5	4	5	4
	Air Circulation	CMH	1200	1200	1200	700	700
	Moisture Removal	L/hr	1.7	1.7	1.6	1.0	1.0
Refrigerant	R-22 / R-410 / R-32	-	R-32	R-32	R-32	R-32	R-32
Heat Exchanger	Copper / PFC	-	Copper	Copper	Copper	Copper	Copper
Noise level	IDU Fan Speed (T/H/M/L/Q)	dB	50/47/44/41/34	50/47/44/41/34	50/47/44/41/34	39/37/34/31/25	39/37/34/31/25
Net Dimensions	Width X Depth X Height	Indoor (mm)	1008*225*318	1008*225*318	1008*225*318	865*200*290	865*200*290
	Width X Depth X Height	Outdoor (mm)	860*345*550	860*345*550	860*345*550	780*295*545	780*295*545
Net Weight	Indoor	Kg	12	12	12	10	10
	Outdoor	Kg	34.0	29.3	24.4	22.2	22
Intelli Convertible 7-in-1	-	-	NA	Yes	Yes	Yes	Yes

# CLEAN COOL+ SERIES



1.5 Ton - 3 Star



**5 YEARS**  
Comprehensive  
Warranty

**HSU18C-TQB3BE1-INV**



1.5 Ton - 4 Star



**5 YEARS**  
Comprehensive  
Warranty

**HSU18C-TQG4BE1-INV**



1.5 Ton - 3 Star



**5 YEARS**  
Comprehensive  
Warranty

**HSU18C-TQS3BE1-INV**



## KEY FEATURES



Supersonic  
Cooling in 10 Sec.

**Triple  
inverter+**

Triple Inverter  
Plus Technology

**7<sup>IN</sup>1**

Intelli  
Convertible 7 in 1



Hyper PCB



Super  
Anti-Corrosion

**60°C**

Cooling at Extreme  
Temperature



12 years  
compressor warranty\*

SPECIFICATION	DESCRIPTION	UNITS	CLEAN COOL+		
			HSU18C-TQG4BE1-INV	HSU18C-TQS3BE1-INV HSU18C-TQB3BE1-INV	HSU13C-TQS3BE1-INV HSU13C-TQG3BE1-INV HSU13C-TQB3BE1-INV
		<b>Model Name</b>	HSU18C-TQG4BE1-INV	HSU18C-TQS3BE1-INV HSU18C-TQB3BE1-INV	HSU13C-TQS3BE1-INV HSU13C-TQG3BE1-INV HSU13C-TQB3BE1-INV
Capacity	Max Cooling	Watts	5400	5400	3850
	100% Cooling	Watts	5100	5070	3450
	50% Cooling	Watts	2550	2535	1725
	Min Cooling	-	750	750	1000
	Heating	Watts	NA	NA	NA
Electrical Rating	Power Supply	Volt/Phase/Hz.	230/Single/50	230/Single/50	230/Single/50
	Power Input (100% Cooling)	Watts	1525	1680	1160
	Rated Current (100% Cooling)	A	6.77	7.45	5.15
Performance	ISEER	W/W	4.45	3.85	3.85
	Energy Star	-	4	3	3
	Air Circulation	CMH	900	900	700
	Moisture Removal	L/hr	1.5	1.5	1.0
Refrigerant	R-22 / R-410 / R-32	-	R-32	R-32	R-32
Heat Exchanger	Copper / PFC	-	Copper	Copper	Copper
Noise level	IDU Fan Speed (T/H/M/L/Q)	dB	44/42/39/37/34	44/42/39/37/34	39/37/34/31/25
Net Dimensions	Width X Depth X Height	Indoor (mm)	910*210*310	910*210*310	865*200*290
	Width X Depth X Height	Outdoor (mm)	780*295*545	780*295*545	780*295*545
Net Weight	Indoor	Kg	11.5	11.5	10
	Outdoor	Kg	24.4	24.4	22
Intelli Convertible 7-in-1	-	-	Yes	Yes	Yes